

3751b While Supplies Last

**SPECIFICATIONS** 

## LOAD CAPACITY

WERNER

TYPE IAA DUTY RATING
Combined Weight of User and Materials

Non-Marring

**Dropped Rail** 

**Pivot Point** 

Secure

Rail Latch

Rubber Bumper Pad

			STEP LADDER MODE		LEANING MODE		
	Model No.	Ladder Size	Max. Standing Height	Avg. Reach Height‡	Max. Standing Height	Avg. Reach Height‡	
\$183.9	<b>9</b> L7306	6 ft	3 ft 10 in	10 ft 1 in	2 ft 10 in	9 ft 1 in	
<b>\$229</b> .	<b>99</b> L7308	8 ft	5 ft 9 in	12 ft 1 in	4 ft 9 in	11 ft 1 in	
\$309.	<b>99</b> L7310	10 ft	7 ft 8 in	14 ft 1 in	6 ft 8 in	13 ft 1 in	

16 ft 1 in

9 ft 7 in

\* assumes a 5 ft 7 in person with a vertical 12 in reach

8 ft 7 in

15 ft 1 in



\$399.99 L7312

Seven-Layer Fiberglass Construction

12 ft



Full Aluminum Bracing



NON-CONDUCTIVE SIDE RAILS FOR USE AROUND ELECTRICITY

Standard step ladders shouldn't be leaned against a wall, but the Werner LEANSAFE® ladder is designed specifically with features to safely lean against a wall, stud, corner, or pole.

## **STANDARD FEATURES:**


- Solid rivets
- Rear horizontals every 12"
- Every step is knee braced
- Internal spreaders
- EDGE360® bracing

🕈 Altoona, PA

2701 Beale Avenue

Slippery Rock, PA

111 Arrowhead Drive



"Solutions is not just part of our name, It's what we strive to achieve"



Different Rail

Colors for Safety